















Single pane			Double pane		Low-E	
						
Not tinted	Tinted	Laminated	Not tinted	Tinted	Low-E	Low-E tinted
						


VLT – visible light transmission **(77%)**

TSER – total solar energy rejected **(18%)**

IRR – Infrared Rejection **(11%)**

UVR-Ultraviolet radiation **(76%)**

Warranty- **10 years**



MULTI COLOR film is effective at reducing solar heat gain. While at the same time continuing to allow over 70% of the natural light in. **MULTI COLOR** film helps reduce solar glare, and at the same time adding beautiful rainbow tone to your windows.

Installation Infinity films are installed using water and a soap. The film drying time is approximately 20 days at 18°C (in dry conditions).

Cleaning Infinity films may be cleaned 1 month after installation using ordinary window cleaning tools. Do not use rough sponges, cloths or brushes. Synthetic sponges, soft wipes or rubber squeegee cleaners are recommended. Do not clean Infinity films dry.

Storage information:

Shelf life is approximately 5 years from the manufacturing date. Films should be stored in its original packaging, laying in a horizontal, away from direct sunlight. Heavy objects are not allowed to place on top of it to avoid damaging the window tint. Recommended storage conditions are +20°C and 50% relative humidity. Avoid extreme temperature ranges in storage.